



Italian Design



ZYMBO ITALIA

USA - Canada

Air conditioner without outdoor unit

Not Much To See On the Outside

This packaged heat pump unit is ideal for installations where the outside façade of a building must be maintained or minimally disturbed. It is suitable for new construction, existing buildings, and historical facilities, commercial, institutional, or residential. It is a wonderful replacement for TTW and PTAC units.



Technical Data

Silent Inverter	Silent Hybrid	Climapuro
-----------------	---------------	-----------

Cooling

Indoor: 80°F, W.B. 67°F; Outdoor: 95°F, W.B. 75°F

Cooling capacity (min-max)	BTU/h	3410-8831
Cooling capacity nominal	BTU/h	8.000
Input Power	W	750
Efficiency	EER	10,60
	IEER	13,80

Heating 47°C

Indoor: 70°F, W.B. 60°F; Outdoor: 47°F, W.B. 43°F

Heating capacity (min-max)	BTU/h	3500-8800+5100 PTC electric
Heating capacity Nominal	BTU/h	8000 + 5100 PTC Electric
Water exchanger	BTU/h	7161
Input Power	W	700
Efficiency	COP	3,35

Airflow

Indoor	Type	DC inverter motor + Aluminium cross fan		
	CFM	150-290		
	Speed	Low-med-high-auto		
	Filter	MERV 3 standard - Optional Merv 7		
Outdoor	Type	ECM Centrifugal Radial		
	CFM	200-350		
	Intake - Exhaust	6" round		
	Speed	0-10 VDC signal		
	Filter	MERV 3	MERV 3	MERV3 + ESP electronic
	Filter Optional	Anti covid filter		

Compressor

Type		DC Inverter
Refrigerant	CFM	R32

Sound

Indoor	db(A)	35-45
Outdoor	db(A)	35-55

Electrical

Volt range	V	207-251
Hz/phase	Hz	50-60 Hz single phase
Power cord		Hardwired
Power factor	%	0,96
Cooling nominal	A	3,40
Cooling max	A	4,90
Heating rated	A	3,30
Heating max (Heating pump + PTC electric)	A	9,56

Dimension

Dimensions	Net	39.37" W x 21.65" H x 6.299" D
	Gross	45.66" W x 25.1" H x 10" D
Weight	Net	101,4 lb
	Gross	116,8 lb
Cabinet	Material	Steel galvanized + painted + crystal
	Finish	White

Zymbo Italia S.r.l.

Via Ponte Musia 23-25
25086 Rezzato (BS) - Italy
www.zymbo.eu
Phone : +39 - 030 0979701

